



Safra
*Shine*TM

WOOD VARNISH



SPECIFICATIONS



Safra Shine™

Transparent
(For Interior & Exterior Use)

Description:

Safra Shine™ is a product with outstanding properties for the protection & decoration of furniture-and other wooden surfaces.

Composition:

Safra Shine™ is composed of high quality poly-urethane alkyd resin, non-toxic odorless solvent and additives of finest possible grade.

Specification:

Boiling Range	:	Not reported
Freezing Point	:	-
Specific Gravity (Water = 1)	:	0.85-0.95
Vapor Density (Air = 1)	:	-
Vapor Pressure (mPa)	:	Not defined
Solubility in Water	:	Insoluble
Evaporation (Butyl Acetate = 1)	:	Not reported
Density (25°C)	:	0.85-0.90
F.P.	:	>40°C
Colour	:	Light yellow/brown

Uses:

Interior

Furniture, wall panels, floors, shelves, cup-boards, doors, windows, veneers, ceiling hand-rail & frames (misc.), etc. all made of wood.

Exterior

Protection grill, sunshades, outer window & door panels, guard fences, etc.



Advantages:

- 1) Transparent
- 2) Matt to Midsheen to full gloss
- 3) Controls water vapor diffusion
- 4) Prevents mould growth
- 5) Weather resistant
- 6) Contains no lead in any form

Application:

Interior

Apply 2 to 3 coats of Safra Shine™ depending upon the absorbency of the surface, by brush, roller or spray. Prior to application surface should be thoroughly clean, dry & dust free. On old surface, application can only be exercised after removing loose coatings, thorough cleaning & drying.

Exterior

Apply 2 coats of colored Safra Shine™ and 1 coat (final) of transparent Safra Shine™ for extra protection by brush, roller or spray.

Coverage: 11-13 Sq. meter/liter (41-49 Sq. meter/USG)

Drying Time : 4-6 hours (Tack-Free)

20-24 hours (Hard dry) – Re-coatability

Equipment Cleaning: Use Safra Odorless Paint Thinner or White Spirit

Note:

Values indicated describe typical properties and do not constitute specification limits.